

Troliu LIFT Winch S6000 - 2948 KG



6000LBS FEATURES AND SPECIFICATIONS	
Rated line pull	6000LB (2948 KG) single line
Motor	4.0kw/5.5hp (12V) permanent magnet
Control	Remote switch, 12ft (3.7m) lead
Gear train	3 Stage Planetary
Gear reduction ratio	218:1
Clutch	Sliding Ring Gear
Braking Action	Automatic In-The-Drum
Drum Size	F2.5"x5.5"(F63.5x140mm)
Cable	9/32" of 66ft diameter (F6.4mmx20m)
Remote Control	Included
Battery	Recommended: 650CCA minimum for winching
Battery Leads	2 gauge, 72"(183mm)
Finish	Black powder coat
Overall Dimensions	17.7"x6.1"x8.6"(449.5mmx156mmx215mm)
Mounting Bolt Pattern	166.4mmx114.3mm
Weight	N.W. 26kg G.W. 28Kg
Packing size	49x19x34.5cm 1PC/CTN

6000LB LINE SPEED AND AMP DRAW (FIRST LAYER) 12V					
Line Pull	lb	0	2000	4000	6000
	kg	0	907	1814	2721
Line Speed	ft/min	28.2	15.4	11.5	9.2
	m/min	8.6	4.7	3.5	2.8
Motor	Amps	70	160	240	310

6000LB LINE PULL AND CABLE CAPACITY				
Layers of cable		1	2	3
Rated line Pull per layer	lb	6000	5500	3700
	kg	2722	2495	1678
Cumulative cable capacity	ft	14.7	29.5	66
	m	4.5	9.0	20