

Troliu LIFT Winch SC9500 wireless: 4300 KG



9500LB FEATURES AND SPECIFICATIONS	
Rated line pull	9500LB (4300 KG) single line
Motor	5.5hp/4.0kw (12V) Series Wound
Control	Remote switch,12ft(3.7m)lead
Gear train	3 Stage Planetary
Gear reduction ratio	218:1
Clutch	Sliding Ring Gear
Braking Action	Automatic In-The-Drum
Drum Size	F2.5"x8.8"(F63.5x224mm)
Cable	5/16" of 94ft diameter (F8.3mmx28m)
Fairlead	4-Way Roller Fairlead
Wireless Remote Control	Optional
Battery	Recommended:650CCA minimum for winching
Battery Leads	2 gauge,72"(183mm)
Finish	Black powder coat
Overall Dimensions	21.1"x6.3"x8.6"(537mmx160mmx218mm)
Mounting Bolt Pattern	254mmx114.3mm
Weight	N.W. 81LB(37kg) G.W. 84LB(38kg)
Packing size	57x19x34.5cm 1PC/CTN

9500LB LINE SPEED AND AMP DRAW (FIRST LAYER) 12V							
Line Pull	lb	NO	2000	4000	6000	8000	9500
	kg	LOAD	907	1814	2721	3628	4300
Line Speed	ft/min	27	15.8	11.7	9.36	7.7	7
	m/min	7.5	4.4	3.25	2.6	2.15	1.95
Motor	Amps	70	145	210	280	350	415

9500LB LINE PULL AND CABLE CAPACITY					
Layers of cable		1	2	3	4
Rated line Pull per layer	lb	9500	7700	6500	5700
	kg	4300	3480	2940	2580
Cumulative cable capacity	ft	16	42	72	94
	m	5	12	21	28